

014613 GPS Antennas - Module Antennas - HAG-140-A -

仕様

Model	HAG-140-A-3V
ANTENNA ELEMENT	
Center Frequency	1575.42 MHz \pm 1.023 MHz
Polarization	R.H.C.P.
Gain @ Zenith	+4dBi typical
Axial Ratio	3dB max
Impedance	50 Ω
LOW NOISE AMPLIFIRE	
Frequency	1575.42 MHz \pm 1.023 MHz
VSWR	Less than 2.0
Impedance	50 Ω
LNA Gain	20dB (\pm 2dB)
Noise Figure	2.0dB (max)
Band Attenuation	20dB min @Fo -50 MHz 15dB min @Fo +50 MHz
Axial Ratio	3dB max
Voltage	DC +3V (\pm 10%)
Current	20mA (max)
MECHANICAL	
Height	6.6 mm
Width	27.0 x 27.0 mm
Cable	RG-174 5m, 1.5D-2V 5m Other Types(Optional)
Connector	SMA Other Types(Optional)
ENVIROMENTAL	
Operating Temp.	-30 $^{\circ}$ C ~ +80 $^{\circ}$ C
Storage Temp.	-40 $^{\circ}$ C ~ +90 $^{\circ}$ C
APPLICATION: Car Navigation	

製品写真



寸法図

